



Vessels Less than 50 meters (165 feet) UL 1104 Certified LED Navigation Lights IMO Resolution MSC 253 (83) 4.3 Compliant

Light Model # example: 0101-PT2ACSN-54

Replacement LED Module # ex: PT2SN

Replacement Power Connector # ex: AC1

Index	Light Type	Nautical Mile	Voltage	Head	Monitor	Mounting Plate
0101-	PT	2	AC	S	N	-54

Light Type	Nautical Mile	Head	Monitor
PT	2	S	N

Voltage	Inputs
AC	1

DC, Double head, Basic (No Monitoring)

0401-PT2DCDN-xx **Port** 112.5* red, 2NM, DC, 2 inputs Double head, no monitoring.

Replacement LED Module # PT2DN

0402- SB2DCDN-xx **Starboard** 112.5* green, 2NM, DC, 2 inputs Double head, no monitoring.

Replacement LED Module # SB2DN

0403- ST2DCDN-xx **Stern** 135* white, 2NM, DC, 2 inputs Double head, no monitoring.

Replacement LED Module # ST2DN

0404- MH5DCDN-xx **Masthead** 225* white, **5NM**, > 20 meters < 50 meters, DC, 2 inputs Double head, no monitoring.

Replacement LED Module # MH5DN

0405- AW2DCDN-xx **All Round** 360* **white**, **2NM**, < 50 meters, DC, 2 inputs Double head, no monitoring.

Replacement LED Module # AW2DN

0406- AW5DCDN-xx **All Round** 360* **white**, **5NM**, **Maneuvering**, DC, 2 inputs Double head, no monitoring.

Replacement LED Module # AW5DN

0407- AG2DCDN-xx **All Round** 360* **green** 2NM, < 50 meters DC, 2 inputs Double head, no monitoring.

Replacement LED Module # AG2DN

0408- AR2DCDN-xx **All Round** 360* **red** 2NM, < 50 meters DC, 2 inputs Double head, no monitoring.

Replacement LED Module # AR2DN

0409- AY2DCDN-xx **All Round** 360* **yellow** 2NM, < 50 meters, DC, 2 inputs Double head, no monitoring.

Replacement LED Module # AY2DN

0410- TW2DCDN-xx **Tow** 135* yellow, 2NM, DC, 2 inputs Double head, no monitoring.

Replacement LED Module # TW2DN

0411- HV2DCDN-xx **Hovercraft** 120fpm 360* yellow, 2NM, DC, 2 inputs Double head, no monitoring.

Replacement LED Module # HV2DN

0412- SP2DCDN-xx **Special Flash** 60fpm 225* yellow, 2NM, DC, 2 inputs Double head, no monitoring.

Replacement LED Module # SP2DN

Replacement Part #s: Power Connector – DC2

Base (two inputs) – Base2

UV Lens – Lens

Mounting Plates: -54 = (5.5" x 5.5" with 4 mounting holes 4" centers)

-5B = (5.5" x 5.5" with no mounting holes (Blank))

-76 = (7" x 7" with 4 mounting holes 6" centers)

-7B = (7" x 7" with no mounting holes (Blank))

Additional options: -PM = 3" pipe mount (mounting plate included)

-VM = vertical mount (mounting plate included)