Signal Mate LLCinfo@SignalMate.comwww.SignalMate.com410-777-5550

Vessels Less than 50 meters (165 feet) UL 1104 Certified LED Navigation Lights IMO Resolution MSC 253 (83) 4.3 Compliant



Light Model #example: 0101-PT2ACSN-54	Replacement LED Module # ex: PT2SN	Replacement Power Connector # ex: AC1
IndexLightNauticalVoltageHeadMonitorMountingTypeMileACSN-54	Light Nautical Head Monitor Type Mile PT 2 S N	Voltage Inputs AC 1

Specialty lights: AC, Double head, Basic (No Monitoring)

Replacement Part #s: Power Connector – AC2	Base (two inputs) – Base2	UV Lens – Lens
0901-GW2ACDN-xx Green & White 360*, 2NM, AC, 2 inputs Double head, no monitoring.		Replacement LED Module # GW2DN
0801-RW2ACDN-xx Red & White 360*, 2NM, AC, 2 inputs Double head, no monitoring.		Replacement LED Module # RW2DN
0701-YW2ACDN-xx Yellow & White 360*, 2NM, AC, 2 inputs Double head, no monitoring.		Replacement LED Module # YW2DN
0601-RG2ACDN-xx Red & Green 360*, 2NM, AC, 2 inputs Double head, no monitoring.		Replacement LED Module # RG2DN

Mounting Plates:	- 54 = (5.5" x 5.5" with 4 mounting holes 4" centers)	- 5B = (5.5" x 5.5" with no mounting holes (Blank))
	-76 = (7" x 7" with 4 mounting holes 6" centers)	- 7B = (7" x 7" with no mounting holes (Blank))
Additional options:	- PM = 3" pipe mount (mounting plate included)	-VM = vertical mount (mounting plate included)