



Vessels Less than 50 meters (165 feet) UL 1104 Certified LED Navigation Lights IMO Resolution MSC 253 (83) 4.3 Compliant

Light Model # example: 0101-PT2ACSN-54

Replacement LED Module # ex: PT2SN

Replacement Power Connector # ex: AC1

Index	Light Type	Nautical Mile	Voltage	Head	Monitor	Mounting Plate
0101-	PT	2	AC	S	N	-54

Light Type	Nautical Mile	Head	Monitor
PT	2	S	N

Voltage	Inputs
AC	1

### Specialty lights: DC, Double head, Basic (No Monitoring)

1001-RG2DCDN-xx Red & Green 360\*, 2NM, DC, 2 inputs Double head, no monitoring.

Replacement LED Module # RG2DN

1101-YW2DCDN-xx Yellow & White 360\*, 2NM, DC, 2 inputs Double head, no monitoring.

Replacement LED Module # YW2DN

1201-RW2DCDN-xx Red & White 360\*, 2NM, DC, 2 inputs Double head, no monitoring.

Replacement LED Module # RW2DN

1301-GW2DCDN-xx Green & White 360\*, 2NM, DC, 2 inputs Double head, no monitoring.

Replacement LED Module # GW2DN

Replacement Part #s: Power Connector –DC2

Base (two inputs) – Base2

UV Lens – Lens

Mounting Plates: -54 = (5.5" x 5.5" with 4 mounting holes 4" centers)

-5B = (5.5" x 5.5" with no mounting holes (Blank))

-76 = (7" x 7" with 4 mounting holes 6" centers)

-7B = (7" x 7" with no mounting holes (Blank))

Additional options: -PM = 3" pipe mount (mounting plate included)

-VM = vertical mount (mounting plate included)