



Vessels Less than 50 meters (165 feet) UL 1104 Certified LED Navigation Lights IMO Resolution MSC 253 (83) 4.3 Compliant

Light Model # example: 0101-PT2ACSN-54

Replacement LED Module # ex: PT2SN

Replacement Power Connector # ex: AC1

Index	Light Type	Nautical Mile	Voltage	Head	Monitor	Mounting Plate
0101-	PT	2	AC	S	N	-54

Light Type	Nautical Mile	Head	Monitor
PT	2	S	N

Voltage	Inputs
AC	1

### DC, Double head, Monitoring

1701-PT2DCDM-xx **Port** 112.5\* red, 2NM, DC, 2 inputs Double head, monitoring.

Replacement LED Module # PT2DM

1702- SB2DCDM-xx **Starboard** 112.5\* green, 2NM, DC, 2 inputs Double head, monitoring.

Replacement LED Module # SB2DM

1703- ST2DCDM-xx **Stern** 135\* white, 2NM, DC, 2 inputs Double head, monitoring.

Replacement LED Module # ST2DM

1704- MH5DCDM-xx **Masthead** 225\* white, **5NM**, > 20 meters < 50 meters, DC, 2 inputs Double head, monitoring.

Replacement LED Module # MH5DM

1705- AW2DCDM-xx **All Round** 360\* **white**, **2NM**, < 50 meters, DC, 2 inputs Double head, monitoring.

Replacement LED Module # AW2DM

1706- AW5DCDM-xx **All Round** 360\* **white**, **5NM**, **Maneuvering**, DC, 2 inputs Double head, monitoring.

Replacement LED Module # AW5DM

1707- AG2DCDM-xx **All Round** 360\* **green** 2NM, < 50 meters DC, 2 inputs Double head, monitoring.

Replacement LED Module # AG2DM

1708- AR2DCDM-xx **All Round** 360\* **red** 2NM, < 50 meters DC, 2 inputs Double head, monitoring.

Replacement LED Module # AR2DM

1709- AY2DCDM-xx **All Round** 360\* **yellow** 2NM, < 50 meters, DC, 2 inputs Double head, monitoring.

Replacement LED Module # AY2DM

1710- TW2DCDM-xx **Tow** 135\* yellow, 2NM, DC, 2 inputs Double head, monitoring.

Replacement LED Module # TW2DM

1711- HV2DCDM-xx **Hovercraft** 120fpm 360\* yellow, 2NM, DC, 2 inputs Double head, monitoring.

Replacement LED Module # HV2DM

1712- SP2DCDM-xx **Special Flash** 60fpm 225\* yellow, 2NM, DC, 2 inputs Double head, monitoring.

Replacement LED Module # SP2DM

**Replacement Part #s:** Power Connector – DC2

Base (two inputs) – Base2

UV Lens – Lens

Mounting Plates: **-54** = (5.5" x 5.5" with 4 mounting holes 4" centers)

**-5B** = (5.5" x 5.5" with no mounting holes (Blank))

**-76** = (7" x 7" with 4 mounting holes 6" centers)

**-7B** = (7" x 7" with no mounting holes (Blank))

Additional options: **-PM** = 3" pipe mount (mounting plate included)

**-VM** = vertical mount (mounting plate included)