



Vessels Less than 50 meters (165 feet) UL 1104 Certified LED Navigation Lights IMO Resolution MSC 253 (83) 4.3 Compliant

Light Model # example: 0101-PT2ACSN-54

Replacement LED Module # ex: PT2SN

Replacement Power Connector # ex: AC1

Index	Light Type	Nautical Mile	Voltage	Head	Monitor	Mounting Plate
0101-	PT	2	AC	S	N	-54

Light Type	Nautical Mile	Head	Monitor
PT	2	S	N

Voltage	Inputs
AC	1

### AD = AC & DC, Double head, Monitoring

2001-PT2ADDM-xx **Port** 112.5\* red, 2NM, AD, 2 inputs Double head, monitoring.

Replacement LED Module # PT2DM

2002-SB2ADDM-xx **Starboard** 112.5\* green, 2NM, AD, 2 inputs Double head, monitoring.

Replacement LED Module # SB2DM

2003-ST2ADDM-xx **Stern** 135\* white, 2NM, AD, 2 inputs Double head, monitoring.

Replacement LED Module # ST2DM

2004-MH5ADDM-xx **Masthead** 225\* white, **5NM**, > 20 meters < 50 meters, AD, 2 inputs Double head, monitoring.

Replacement LED Module # MH5DM

2005-AW2ADDM-xx **All Round** 360\* **white**, **2NM**, < 50 meters, AD, 2 inputs Double head, monitoring.

Replacement LED Module # AW2DM

2006-AW5ADDM-xx **All Round** 360\* **white**, **5NM**, **Maneuvering**, AD, 2 inputs Double head, monitoring.

Replacement LED Module # AW5DM

2007-AG2ADDM-xx **All Round** 360\* **green** 2NM, < 50 meters AD, 2 inputs Double head, monitoring.

Replacement LED Module # AG2DM

2008-AR2ADDM-xx **All Round** 360\* **red** 2NM, < 50 meters AD, 2 inputs Double head, monitoring.

Replacement LED Module # AR2DM

2009-AY2ADDM-xx **All Round** 360\* **yellow** 2NM, < 50 meters, AD, 2 inputs Double head, monitoring.

Replacement LED Module # AY2DM

2010-TW2ADDM-xx **Tow** 135\* yellow, 2NM, AD, 2 inputs Double head, monitoring.

Replacement LED Module # TW2DM

2011-HV2ADDM-xx **Hovercraft** 120fpm 360\* yellow, 2NM, AD, 2 inputs Double head, monitoring.

Replacement LED Module # HV2DM

2012-SP2ADDM-xx **Special Flash** 60fpm 225\* yellow, 2NM,AD, 2 inputs Double head, monitoring.

Replacement LED Module # SP2DM

Replacement Part #s: Power Connector – AD2

Base (two inputs) – Base2

UV Lens – Lens

Mounting Plates: -54 = (5.5" x 5.5" with 4 mounting holes 4" centers)

-5B = (5.5" x 5.5" with no mounting holes (Blank))

-76 = (7" x 7" with 4 mounting holes 6" centers)

-7B = (7" x 7" with no mounting holes (Blank))

Additional options: -PM = 3" pipe mount (mounting plate included)

-VM = vertical mount (mounting plate included)