Signal Mate LLC	info@	SignalMate.com	www.Sign	alMate.com	410-777-5550	
Vessels 50 meters (165 feet) a	nd Up	UL 1104 Certified LED Nav	igation Lights	IMO Resolution MS	C 253 (83) 4.3 Compliant	



Light Model #example: 5101-PT3ACSN-54	Replacement LED Module # ex: PT3SN	Replacement Power Connector # ex: AC1
Index Light Nautical Voltage Head Monitor Mounting Type Mile Plate 5101- PT 3 AC S N -54	Light Nautical Head Monitor Type Mile PT 3 S N	Voltage Inputs AC 1

Specialty lights: AC, Double head, Basic (No Monitoring)

5601-RG3ACDN-xx Red & Green 360*, 3NM, AC, 2 inputs Double head, no monitoring.	Replacement LED Module # RG3DN
5701-YW3ACDN-xx Yellow & White 360*, 3NM, AC, 2 inputs Double head, no monitoring.	Replacement LED Module # YW3DN
5801-RW3ACDN-xx Red & White 360*, 3NM, AC, 2 inputs Double head, no monitoring.	Replacement LED Module # RW3DN
5901-GW3ACDN-xx Green & White 360*, 3NM, AC, 2 inputs Double head, no monitoring.	Replacement LED Module # GW3DN

Replacement Part #s: Power Connector – AC2Base (two inputs) – Base2UV Lens – Lens

Mounting Plates:	- 54 = (5.5" x 5.5" with 4 mounting holes 4" centers)	- 5B = (5.5" x 5.5" with no mounting holes (Blank))	
	-76 =(7" x 7" with 4 mounting holes 6" centers)	- 7B =(7" x 7" with no mounting holes (Blank))	
Additional options:	-PM = 3" pipe mount (mounting plate included)	-VM = vertical mount (mounting plate included)	