



Vessels **50 meters (165 feet) and Up** UL 1104 Certified LED Navigation Lights IMO Resolution MSC 253 (83) 4.3 Compliant

Light Model # example: 5101-PT3ACSN-54

Replacement LED Module # ex: PT3SN

Replacement Power Connector # ex: AC1

Index	Light Type	Nautical Mile	Voltage	Head	Monitor	Mounting Plate
5101-	PT	3	AC	S	N	-54

Light Type	Nautical Mile	Head	Monitor
PT	3	S	N

Voltage	Inputs
AC	1

New – DC, 1 input, A = Double head – Alternates & Automatic, Monitoring

6901-PT3DCAM-xx **Port** 112.5* red, 3NM, DC, 1 input **Alter/Auto**, monitoring.

Replacement LED Module # PT3AM

6902-SB3DCAM-xx **Starboard** 112.5* green, 3NM, DC, 1 input **Alter/Auto**, monitoring.

Replacement LED Module # SB3AM

6903-ST3DCAM-xx **Stern** 135* white, 3NM, DC, 1 input **Alter/Auto**, monitoring.

Replacement LED Module # ST3AM

6904-MH6DCAM-xx **Masthead** 225* white, **6NM**, > 50 meters, DC, 1 input **Alter/Auto**, monitoring.

Replacement LED Module # MH6AM

6905-AW3DCAM-xx **All Round** 360* **white**, **3NM**, > 50 meters, DC, 1 input **Alter/Auto**, monitoring.

Replacement LED Module # AW3AM

6906-AW5DCAM-xx **All Round** 360* **white**, **5NM**, **Maneuvering**, DC, 1 input **Alter/Auto**, monitoring.

Replacement LED Module # AW5AM

6907-AG3DCAM-xx **All Round** 360* **green** 3NM, > 50 meters DC, 1 input **Alter/Auto**, monitoring.

Replacement LED Module # AG3AM

6908-AR3DCAM-xx **All Round** 360* **red** 3NM, > 50 meters DC, 1 input **Alter/Auto**, monitoring.

Replacement LED Module # AR3AM

6909-AY3DCAM-xx **All Round** 360* **yellow** 3NM, > 50 meters, DC, 1 input **Alter/Auto**, monitoring.

Replacement LED Module # AY3AM

6910-TW3DCAM-xx **Tow** 135* yellow, 3NM, DC, 1 input **Alter/Auto**, monitoring.

Replacement LED Module # TW3AM

6911-HV3DCAM-xx **Hovercraft** 120fpm 360* yellow, 3NM, DC, 1 input **Alter/Auto**, monitoring.

Replacement LED Module # HV3AM

6912-SP2DCAM-xx **Special Flash** 60fpm 225* yellow, 2NM, DC, 1 input **Alter/Auto**, monitoring.

Replacement LED Module # SP2AM

Replacement Part #s: Power Connector – DC1

Base (one input) – Base1

UV Lens – Lens

Mounting Plates: **-54**=(5.5" x 5.5" with 4 mounting holes 4" centers)

-5B = (5.5" x 5.5" with no mounting holes (Blank))

-76=(7" x 7" with 4 mounting holes 6" centers)

-7B=(7" x 7" with no mounting holes (Blank))

Additional options: **-PM** = 3" pipe mount (mounting plate included)

-VM = vertical mount (mounting plate included)